

Optical Filters and Coatings

Engineered & Manufactured to the Highest Industry Standards in the World



Why choose Andover Corporation?

Andover Corporation was established in 1976 with the purpose of designing and manufacturing high-quality optical filters and coatings. Over the years as the company has grown, the focus has remained on quality and service. Our current facility spans 44,000 square feet on 17 acres of land in Salem, NH.

Our facility is custom-designed and state-of-the-art, and includes automated coating, glass polishing, and fabrication equipment. Our testing capabilities are extensive, including both automated spectrophotometers for broadband spectral measurements and ultra-high resolution spectrophotometers for narrowband measurements. Our optical metrology lab features a custom designed, computer-controlled tunable interferometer to measure transmitted wave fronts beyond the capabilities of a traditional laser interferometer.

We manufacture filters and coatings for a wide variety of applications, including medical instrumentation, fluorescence studies, machine vision, agricultural imaging, ground-based and space-borne astronomical observation, telecommunications, military and civilian surveillance systems and defense targeting systems.


Our worldwide exposure currently reaches Belgium, Canada, China, Denmark, Finland, France, Germany, Hong Kong, India, Ireland, Italy, Japan, Korea, Netherlands, Norway, Poland, Russia, Spain, Sweden, Switzerland, Taiwan, United Kingdom, and many other countries.




Integrated Capabilities

Andover has developed in-house integrated capabilities from prototype design through fabrication, coating, testing and assembly.

This integrated capability results in shorter lead times than industry averages and better control over quality.









Market Segments & Applications

Markets

- Defense & Aerospace
- **Environmental**
- Science & Industry
- Instrumentation
- Astronomy
- Semiconductor
- Imaging
- Biotechnology
- Medical Devices
- Universities & National Labs
- Resellers & Representatives



Lockheed Martin



- Surveillance and targeting
- Night vision systems
- **Environmental** monitoring
- Oil/Water/Gas analysis
- Agricultural imaging
- Fluorescence studies
- Spectroscopy
- Thermal imaging
- Astronomy







Optical Coating Capabilities

All coating chambers are proprietary, custom built, and internally-designed. We have multiple chambers for each technology.

Combining these technologies allows us to create unique coating solutions.

Substrate Materials

- BK-7; H2; G-18
- Fused silica; UV & IR grade
- Filter glass
- Sapphire
- Germanium
- Zinc Sulfide
- Zinc Selenide
- Silicon, CZ and FZ grade
- Calcium Fluoride
- Barium Fluoride
- Magnesium Fluoride

1). Magnetron Sputtering

- Extremely stable coatings
- Low water-content coatings

2). E-Beam with Ion Assist

- · Low-priced, hard-coated optics
- Chambers can coat up to 14"

3). Resistance Evaporation

- Low cost option
- Various coating types available

4). Hybrid Technologies

Great for custom applications and prototyping



Magnetron Sputtering

Wavelengths: UV-Mid IR 300nm to 5000nm

Sizes: 2mm to 200mm

Products

- Windows
- Lenses
- Mirrors
- Beamsplitters
- AR and BBAR Coatings
- Prisms
- Laser optics
- Bandpass filters
- Long & shortpass filters
- Dichroic filters
- Multiband AR's

Benefits

- Environmentally stable and extremely durable
- No W/L shift over time
- Consistent production results
- Low water-content coatings
- Complicated requirements





E-Beam with Ion-assist

Wavelengths: UV-Mid IR 240nm to 2500nm

Sizes: 2mm to 355mm

Products

- Windows
- Lenses
- Mirrors
- Beamsplitters
- AR coatings
- Prisms
- Long & shortpass filters
- Dichroic filters
- Image quality filters
- Neutral density filters; UV, VIS, NIR, IR
- Laser coatings

Benefits

- Durable and environmentally stable
- Large usable coated area for large optics
- Stress-free coatings for low-surface distortion
- Parts coated to size for low unit cost
- Improved UV transmission
- High laser damage threshold






Resistance Evaporation

Wavelengths: UV-Near IR 193nm to 2400nm Sizes: 5mm to 250mm

Products

- Image quality filters
- Bandpass filters
- Wideband filters
- Ultra-narrowband filters
- UV filters




Benefits

- Lower cost
- Short lead times
- Variety of coating types available
- Ultra-narrowband selections <0.1nm in the VIS
- Parts coated to size
- Low distortion for imaging applications




Specially Developed (IR) Coatings




Custom IR Edge Filters

- 2-14µm range
- Custom product available
- Dichroic edge filters
- Used for beamsplitters



Narrowband Filters

- 2-14µm range
- Bandwidths as low as 1% of center wavelength




Dual-Band IR Coating

- Transmits 3-5µm and 8-12µm
- Used for combination targeting and thermal imaging applications
- Other wavelengths available



Products & Services

- Custom optics from 193nm 15000nm
- Catalog optical filters from 193nm 10600nm
- Custom bandpass filters from 240nm 14000nm
- Optical accessory products
- Design support for custom applications and R&D services
- Measuring services
- Optical assemblies
- Substrate fabrication
- Dicing
- Precision beveling





Catalog – Filters & Accessories

Standard wavelengths: 193nm – 10600nm / Sizes: 12.5mm to 50mm

Bandpass Filters

Standard and Custom First-surface UV filters High transmitting Hard-coated

Infrared Filters

Bandpass filters Neutral density filters Edge filters

Heat Control Filters

Ultraviolet cold mirrors Cold mirrors Hot mirrors Infrared suppressing filters

24/7 ONLINE ORDERING!

www.andovercorp.com

Neutral Density Filters

Metallic UV-VIS-NIR Infrared ND filters ND filter sets Absorptive ND filters

Dichroic Filters

Color-control filters

Steep-Edge Longpass Filters

Slope <1% Deep blocking

Standard Edge Filters

Long wave pass Short wave pass

Accessories

Threaded rings
Motorized and manual filter wheels
Temperature controllers



Manual & Motorized Filter Wheels

With the smallest footprint of their kind, our filter wheels can be used for a variety of applications, including;

- Color CCD photography
- Fluorescence microscopy
- Photometry Measuring colors and intensity of light

Features

- Motorized and manual
- Compact footprint
- Local or remote control
- Labeled filtered positions
- Base and post mountable
- Programmable filter sequences
- Two 4" diameter wheels available;
 12.5mm and 25mm





Temperature Controller

Protects against the influences of fluctuating ambient temperatures and enables fine tuning of bandpass filters

General Specifications

Regulation Accuracy: +/-0.25° C

Ambient Temperature Range: 0° C - 40° C

• Min. Regulated Temperature: 30° C

• Max. Regulated Temperature: 60° C

• Filter Sizes: 50mm and 75mm Dia.

<u>Features</u>

Custom sizes available

Ovens available with or without bandpass filters





Quality Control

Spectrophotometers

- Cary 500, 5000 & 7000:UV-VIS-NIR
 Spectral Range 193nm 33000nm
- PE 983G NIR-MWIR-LWIR
 Spectral Range 2000nm 56000nm
- PE Frontier Optica, FTIR
 Spectral Range 15000nm 25000nm
- Spex 1.26 meter for ultra-narrowband filters (VIS-NIR)
 Spectral Range 193nm 1200nm, 0.0025 Resolution

Inspection & Testing

- Mitutoyo optical comparator
- Near-infrared inclusion tester
- Janis cryostat tunable from 77°K to 500°K
- Custom-made tunable white light interferometer
- Zygo laser interferometers
- Environmental test chambers humidity and temperature cycling
- Optical alignment testing capabilities
- Custom testing & inspection





Grinding, Polishing & Fabrication

- Diamond surface grinders
- Myford cylindrical grinders
- Strasbaugh single-sided polishers
- Speedfam double-sided polishers
- Speedfam double-sided diamond lappers
- Automated lens centering machines for high precision beveling
- Dicing
- Haas CNC fabrication centers
 - -Coring -Milling
 - -Sawing -Shaping



Valued Customers











































Quality Assurance

Andover Corporation's Quality System is Certified to;

ISO 9001: 2015

AS9100: 2016









Additional details

Cage Code: 0J798

Duns no: 09-427-6854

EIN: 04-2607555

SIC Codes: 3827 Optical Instruments & Lenses

NAICS code: 333314 Optical Instrument & Lens Manufacturing

Andover Contacts
Phil Clark
Technical Sales

Technical Sales pclark@andovercorp.com

Rob Pursel
Senior Optical Engineer
rpursel@andovercorp.com

Sue Brennan
Inside Sales
sue.brennan@andovercorp.com

Nicole Christensen
Sales Coordinator
nicole.christensen@andovercorp.com

Tina Hoppock
Senior Sales Engineer
Tina.hoppck@andovercorp.com

Michael Tiner
Chief Operating Officer
mtiner@andovercorp.com

Thank you!



4 Commercial Drive, Salem NH 03079

T: 603.893.6888 • F: 603.893.6508 • www.andovercorp.com